

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
12 August 2004 (12.08.2004)

PCT

(10) International Publication Number
WO 2004/067287 A1

(51) International Patent Classification²: B41M 5/00, B41J 2/01 (72) Inventor; and
(75) Inventor/Applicant (for US only): KAWANO, Kenichi [JP/JP]; c/o CANON FINETECH INC., 5540-11, Sakatemachi, Mtsukaido-shi, Ibaraki 303-8503 (JP).

(21) International Application Number: PCT/JP2003/015893 (74) Agents: YOSHIDA, Katsuhiro et al.; AKOSU BUILDING, 30, Kanda Sakuma-cho 3-chome, Chiyoda-ku, Tokyo 101-0025 (JP).

(22) International Filing Date: 11 December 2003 (11.12.2003) (81) Designated States (national): CN, US.

(25) Filing Language: English (84) Designated States (regional): European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR).

(26) Publication Language: English (85) Published: — with international search report

(30) Priority Data:
2003-019179 28 January 2003 (28.01.2003) JP
2003-021052 29 January 2003 (29.01.2003) JP
2003-022504 30 January 2003 (30.01.2003) JP

(71) Applicant (for all designated States except US): CANON FINETECH INC. [JP/JP]; 5540-11, Sakatemachi, Mtsukaido-shi, Ibaraki 303-8503 (JP).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

WO 2004/067287 A1

(54) Title: IMAGE RECORDING METHOD

(57) Abstract: An image recording method is disclosed. To form an image, an ink is caused to adhere on a recording medium which is provided with at least one ink-receiving layer on a base material. The ink is an inkjet recording ink, which is composed of a high-molecular dispersant, a water-insoluble colorant, a water-soluble organic solvent and water. The high-molecular dispersant contains at least one hydrophobic block and at least one hydrophilic block. The ink-receiving layer contains fine inorganic particles and a water-soluble resin and/or water-dispersible resin, and a surface pH of the ink-receiving layer is controlled within a range of from 3.0 to 6.5.